

TECHNICAL SPECIFICATIONS*	500CC
ENGINE	Four Stroke, OHV
BORE & STROKE	84mm x 90mm
CUBIC CAPACITY	499 CC
COMPRESSION RATIO	6.5:1
ENGINE OUTPUT / TORQUE	22 BHP @ 5400 RPM 3.5 kgm / 3000 RPM
ELECTRICAL	12 Volts
IGNITION	Battery & Coil
LUBRICATION	Dry Sump Positive Plunger Type
CLUTCH	Multiplate - Oil immersed
TRANSMISSION	4 Speed - Constant Mesh
GEAR SHIFT	Lever Operated - LH side 1 Down & 3 Up
SUSPENSION	Front: Telescopic- Hydraulic Rear: Twin Shock Absorbers
BRAKES	Front: Twin Lead - Drum 7" Rear: Drum 6" Pedal Operated RH side
TIRES	Front: 3.25 x 19 Rear: 3.50 x 19
TANK CAPACITY	14.5 Ltrs. / 3.8 gal.
RESERVE	1.25 Ltrs. / .33 gal.
FUEL CONSUMPTION	**70 mpg - 25 Km/Ltr

DIMENSION (L x W x H)	2110 x 700 x 1067 mm 82 1/4 x 27 1/4 x 41-1/2 in.
WHEEL BASE	1372 mm / 53 1/2 in.
GROUND CLEARANCE	140 mm / 5 1/2 in.
SEAT HEIGHT	760 mm / 30 in.
MAXIMUM SPEED	125 KM/H
DRY WEIGHT	168 kgs

